

DYNA

Portable Generators by **WINCO**[®]



D3000H



DL6000I

DYNA FEATURES

- PREMIUM CARB/EPA APPROVED HONDA OR BRIGGS & STRATTON ENGINES
- ALL COPPER WINDINGS AND CIRCUIT BREAKERS FOR OPERATOR SAFETY AND PROTECTION AGAINST DAMAGING OVERLOADS
- STURDY WRAP-AROUND WELDED TUBULAR CRADLES
- DURABLE, LONG LASTING POWDER PAINT FINISH
- LIGHT, COMPACT DESIGN FOR CONVENIENT STORAGE AND TRANSPORT
- LARGE FUEL TANKS FOR LONGER RUN TIMES (5kW AND LARGER)
- SIZES RANGING FROM 3kW TO 9kW

WINCO INC[®]
A Division of **DTI** Dyna Technology Inc

Sommers Motor Generator Sales Ltd.
101 Woodstock St. S.
Tavistock, ON, N0B 2R0
Ph: 519-655-2396 Fax: 519-655-3176
Toll Free: 1-800-690-2396
www.sommersgen.com



D3000H



DL5000H



DL6000I



DL9000E

PERFORMANCE & TECHNICAL DATA

| Model Number | D3000H | DL5000H | DL6000H/ DL6000IE | DL6000I | DL9000E |
|--------------|--------|---------|----------------------|---------|---------|
|--------------|--------|---------|----------------------|---------|---------|

Electrical Specifications

| | | | | | |
|----------------------------|------------|----------------|----------------|----------------|----------------|
| Maximum Power Rating | 3000 watts | 5000 watts | 6000 watts | 6000 watts | 9000 watts |
| Continuous Power Rating** | 2300 watts | 4500 watts | 5500 watts | 5500 watts | 8000 watts |
| A.C. Output Voltage | 120 volts | 120/240 volts | 120/240 volts | 120/240 volts | 120/240 volts |
| Continuous Current Rating | 19.1 amps | 37.4/18.7 amps | 45.8/22.9 amps | 45.8/22.9 amps | 66.7/33.3 amps |
| Motor Starting Ability (1) | .75 hp | 1.5 hp | 1.5 hp | 2 hp | 4 hp |

Engine Data

| | | | | | |
|------------------------|-------------|-------------|-------------|-------------|-----------------|
| Make/Model | Honda GC160 | Honda GX270 | B&S/intek | Honda GX340 | B&S/Vanguard |
| Displacement/Type | 160 cc/OHC | 270 cc/OHV | 342 cc/OHV | 337 cc/OHV | 480 cc/OHV |
| Rated Power (3600 RPM) | 5 hp | 9 hp | 11 hp | 11 hp | 16 hp |
| Starting System (2) | Recoil | Recoil | (3) | (3) | Electric/Recoil |
| Fuel Tank Capacity | 2 Qt. | 4.5 Gallons | 4.5 Gallons | 4.5 Gallons | 4.5 Gallons |
| Low Oil Protection | Standard | Standard | Standard | Standard | Standard |
| Running Time-Full Load | 1.1 hours | 6.6 hours | 5.3 hours | 4.5 hours | 3.4 hours |
| Running Time-Half Load | 1.5 hours | 10.3 hours | 8.5 hours | 6.4 hours | 5.6 hours |

120 Volt Receptacles

| | | | | | |
|-----------------------------|----------|----------|----------|----------|----------|
| Straight Blade (NEMA 5-20R) | 2-20 amp | 2-20 amp | 4-20 amp | 4-20 amp | 4-20 amp |
|-----------------------------|----------|----------|----------|----------|----------|

120/240 Volt Receptacles

| | | | | | |
|---------------------------|-----|----------|----------|----------|----------|
| Twist-Lock (NEMA L14-30R) | N/A | 1-30 amp | 1-30 amp | 1-30 amp | 1-30 amp |
|---------------------------|-----|----------|----------|----------|----------|

Size & Weight

| | | | | | |
|--------------------|-----------------|--------------|-------------------|--------------|--------------|
| Dimensions (LxWxH) | 20.75x15x16 in. | 30x19x22 in. | 26.25x18x21.4 in. | 30x22x22 in. | 32x22x22 in. |
| Shipping Weight | 92 lbs. | 150 lbs. | 158/168 lbs. | 202/210 lbs. | 274 lbs. |


Warranty Information - Consumer Application (4)

| | | | | | |
|------------------|------------|-------------|-------------|-------------|-------------|
| Generator/Engine | 2 yrs/1 yr | 2 yrs/2 yrs | 2 yrs/2 yrs | 2 yrs/2 yrs | 2 yrs/2 yrs |
| CSA Approved | Yes | Yes | Yes | No | Yes |

NOTES: (1) Code G Capacitor Start Motor. (2) Electric start models include battery rack and cables. Battery not included.
 (3) Models DL6000I and DL6000H are recoil start only. Models DL6000IE and DL6000HE have both recoil and electric start.
 (4) Commercial or Prime Power (Off-Grid) Warranty - 90 Days; International Warranty

** Power Output +/- 5%

DYNA 6/06



Sommers Motor Generator Sales Ltd.
 101 Woodstock St. S.
 Tavistock, ON, N0B 2R0
 Ph: 519-655-2396 Fax: 519-655-3176
 Toll Free: 1-800-690-2396
 www.sommersgen.com